

HDI-55 EDGE

HDI edge
NEW GENERATION

55" Multi-touch Screen Slim IR

HDI Edge multi touch screens incorporate 20 points of touch with the slimmest IR screen on the market.

Complete with HDi OS Android, the system is completely plug and play, with no drivers necessary for interaction. (Disabled for AVSO)

All HDi screens work with Windows, OSX, Linux Android and Chrome operating systems.

The screen 4K resolution, LED high brightness backlight and wide screen format provides an ideal medium for presentation, interaction and collaboration.

There are ample I/O ports that would suit any audio-visual environment, making the HDi Edge a must-have companion for education, government and the corporate sector.

HDI Edge multi touch screens come ready for easy wall or mobile stand installation.

4K 4K resolution

Slim IR
technology

4 mm
toughened glass

Mobility
Options



Features

- Optical Slim IR Technology
- Powered by HDi OS™ (Built on Android™ 11.0)
- Multi-touch – 20 touch points
- Pre-installed interactive apps
- Integrated inbuilt sound bar
- 4K resolution (3840 x 2160 px)
- HDi Sketch™ app
- Mobile and electric height-adjustable options available
- 3 Year warranty
- Ships with wall-mount bracket



TECHNICAL SPECIFICATIONS

Resolution	Up to 3840 x 2160 @ 60Hz
Display Features	LED backlight
Screen dimension	55" / 1390mm
Set dimension	50.3" (L) x 31.6" (H) x 3.2" (W) / 1279mm(L) x 804mm(H) x 82mm(W) Not including base
Temperature / Humidity	0°C ~ 40° / ≤80%
Net weight	42 +-2KGS / 92.5 lbs
Aspect Ratio	16:9
Brightness	500cd/m2
Contrast	1100:1
Colours	10bit, 1.07 Billion colours
View Angle	89°(V) / 89° (H)
Screen Mode	16:9/4:3/dot to dot/full screen
Video Mode	PAL, NTSC, SECAM
Sound Mode	D/K, B/G, I, M
Support Resolution	1280x960 / 1280x1024 / 1360x768 / 1440x900 / 1600x1200 / 1920x1080 / 3840 x 2160@60Hz (Opt)
Voltage range	AC 240V, v-50/60Hz
Power range	Standby Power <1W - Rated Power < 150W
Audio	15W x 15W internal speakers

INPUTS

CVBS/Audio input	1 x MINI (black)
YPbPr	1 x MINI (black)
SD Card	1 x SD Card
Network	1 x RJ45 / Control LAN
USB input	2 x USB3.0 USB-A (horizontal), 1xUSB 2.0 (front), 1x PC (front), Connect back USB 2.0-A - Vertical
PC RGB input	1 x D-USB 15pin
PC audio input	1 x 3.5 stereo audio-in jack
HDMI input	3 x HDMI-A, one in front
HDMI format	HDMI 2.0(back) HDMI .4 (front) HDCP 1.2
Interactive control input	2 x USB-B, one in front
USB file system	FAT32, FAT16, NTFS (NTFS compressed file is not supported)

OUTPUTS

CVBS/Audio out	1 x MINI (Black)
Headphone	1 x Earphone Jack
SPDIF output	1 x RCA

ANDROID 11.0 SPECIFICATIONS **DISABLED for AVSO**

CPU	2*ARM Cortex-A73 1.5GHz
	2*ARM Cortex-A53 1.5GHz
GPU	ARM Mali-G51 450 MHz
Flash	32GB Build in EMMC
SDRAM	4GB DDR4
Android Version	8.0
SD Card	Support MAX 32GB SD Card
WIFI	IEEE802.11 a/b/g/n 2.4 GHz + 5.0GHz

TOUCH PARAMETERS

Touch points	Up to 20 point multi touch
Writing mode	Finger, stylus or any non-transparent object
Positioning technology	IR technology
Positioning accuracy	+/- 2mm
Positioning resolution	4096 x 4096
Writing response time	First point < 8ms, consecutive < 4ms
Cursor speed	>180 dot/sec
Interactive touch control	USB plug and play
Operating system	Windows / Linux / Mac / Android /Chrome
PC response	System auto response

SCREEN PACKAGE

Dimensions	1400mm (L) x 940mm (H) x 200mm(W)
Gross weight	50KG



Mobility solutions

At HDi we pride ourselves on designing and building customised solutions to solve many bespoke problems.

Remarks:

Above mentioned parameters are for Standard models and are subject to change without notice. * Not all applications are compatible with Android 11.0.

